Product Features

- Hygienic reduces mould & mildew.
- Adds insulation for heat & sound.
- Can be applied to virtually all surfaces - including tiles.
- No grouting.
- Quick, easy and clean to install.
- Easy to clean and maintain.
- Range of versatile profile fittings.
- Can be fitted onto existing ceilings no more painting!

Technical

Specification

- High impact modified u-PVC.
- 8mm twin-wall construction.
- Reaction to fire classification: C s3, d0
- Interlocking, 'tongue and groove' design with a flush flat finish.
- Range of edging and corner profiles.
- Optional finish products borders, coving, skirting, dado.

Cleaning & Maintenance

- Ensure traces of adhesive and silicone sealant are removed from surface of cladding before they set.
- Use a mild soap solution and soft damp cloth to clean.
- Avoid use of abrasive or harsh chemical cleaning agents.
- Please request samples as colours may vary during printing of brochures.
- Colours may vary from batch to batch.

Limitations of Use

- Possible adverse reaction to solvent based adhesives - use recommended adhesives only.
- Application of adhesives, including adhesive tapes, to printed surface is not recommended.
- Exposure to extreme heat source may result in distortion of product.
- Despite a high level of surface proctection, prolonged exposure to U.V. may result in colour variation.

Terms and Conditions can be viewed at www.enviroclad.com/terms

Trims







External Corn

Internal Corner


Flexible Corner


Starter Trim

HOW TO INSTALL

- Ensure walls are clean & dry. Remove loose tiles, loose paper, flaking paint.
- Seal bath trim (if using) into position.
- Fit bottom Starter trim onto Bath seal using sealant (Fig. 1).
- Fill bottom Starter trim with sealant.
- Cut top Starter trim to length, place in position and continue (Fig. 5).
- At a corner, fit Internal Corner Profile, seal with silicone or apply bead of silicone (Figs.2 & 3).
- Cut first plank to length less 10mm, to allow fitting into top and bottom Starter trims (also allows for expansion). • Apply adhesive to reverse of plank - horizontal strips to width of plank, approx. every 400mm.
- Fit plank in position & press firmly onto wall.
- External Corner profiles are available for use on corners if required.
- Ensure adhesive and sealant are cleaned from face of cladding before they set.
- Cladding can be fitted behind radiators but is not suitable for use with a direct heat source, e.g. solid fuel cookers (heat greater than 60°C). A stainless steel or glass panel should be fitted behind cookers/hobs.
- Please refer to the current brochure for full product details.
- Return of goods will be accepted within 30 days with proof of purchase. After 30 days 20% restocking fee will be charged.
- Fitting at the fitter's discretion.







K,

+353 56 7752866





• If cladding shower/over bath, seal lip of each plank with silicone before fitting the next to ensure watertight seal (Fig. 4).

• When fitting cladding to a shower, Starter trim can be used as a stop bead at shower door or to finish edge of the final plank.

• Recessed Lighting: Please note that only PL or CL type low energy downlighters are suitable for use with Enviroclad ceiling panels



DECORATIVE PANELS A MODERN ALTERNATIVE TO TILES

CLADDING & STARTER TRIM — FIG.5

f facebook.com/enviroclad www.enviroclad.com www.shop.enviroclad.com

C +35<u>3</u>567752866 💌 info@enviroclad.com

www.enviroclad.com www.shop.enviroclad.com

f facebook.com/enviroclad



Description

Millennium Range:

Panels to be fitted in sequence 1-4

Panels to be fitted

in sequence 1-4

Panels to be fitted

in sequence 1-4

Internal Corner (optional)

Flexible Angle 25x25mm

pack 4 planks

per plank

pack 4 planks

per plank

pack 4 planks

pack 4 planks

Size

2.7m

2.7m

2.5m

2.7m

3.0m

310ml

310ml

310ml

600ml

1.83m

2.6m

for 600ml foil

20x20mm x 3m White

30x30mm x 3 White

125mm x 2.5m White

70mm x 2.5m White

50mm x 2.4m White

70mm x 2.5m White/Woodgrain

25mm x 2.6m W, Blk, Cream

600 x 400mm S/less Steel

per plank

per plank

NAME:

DATE:

Cladding

Decor:

Elegance:

Impressions:

Trims, etc

Starter Trim

Silicone 799

Adhesive 796

Adhesive Gun

Bath Trim

Angle

Angel

Coving

Skirting Tara

Architrave Tara

Smart Skirting

Dado Rail Joiner

Dado Rail

The Works Adhesive

Adhesive – Foil Pack 796

Window Board – per metre

Stainless Steel Panel

Joiner

External Corner

Decorative PVC wall panels for Showers, Bathrooms and Kitchens No Grouting – Mould and Mildew Resistant – Easy to Install – Adds Insulation – Reduces Condensation

Price List – Supply Only (inclusive of VAT @ 23%) Ex-Stock

Unit Price € Quantity

33.00 8.50

38.00

10.00

43.00

11.50

48.00 12.50

7.75

7.75

4.50

4.50

5.10

5.00

8.50

5.00

7.00

50.00

5.70

4.00

5.00

9.00

20.00

15.00

6.50

40.00

25.00

12.50

Price

Total Due

DIMENSIONS:

CONTACT NO:

Size

1000mm x 2.7m

250mm x 2.7m

Gloss White, Sandstone, Grey, Green, Pink, Beige

1000mm x 2.7m

250mm x 2.7m

Wood Block, White Wash Pine, Marble Tile, Bronze Tile, Stone Tile, Slate Tile

1000mm x 2.7m

250mm x 2.7m

1000mm x 2.7m

250mm x 2.7m

Wave, Stone, Anthracite Tile Small, Anthracite Tile Large, Modern Tile Small, Modern Tile Large

Red Brick, White Brick, Oak, Slate, Bar Mosiac, Customised

White

White

White

White

White

White

n/a

White

White

White/Silver

Colour

White, Black

White, Black

W, Blk, Beige

MILLENNIUM







Sandstone

Green

White Gloss





Pink





Woodblock Bronze

Stone Tile

White Washpine





Slate Tile

Marble Tile

Estimated Cost of Fitting: € Shop online: www.shop.enviroclad.com

Total Cost - Supply Only: €

Delivery service available nationwide — please call for details.



ELEGANCE





Wave

Anthracite Tile Large



Modern Tile Small

Tile Small

Modern


Tile Large



IMPRESSIONS

Oak

ustomised Designs Available



Red Brick White Brick





Slate

Bar Mosiac